





DECORATIVE AND DURABLE

Resisting harsh weather conditions doesn't have to cast a shadow on your design choices. When designing building façades and other aluminium components, we know how important it is to match beauty with durability.

That's why we developed our Jotun Facade line. It offers an incredible range of finishes in five stunning collections that prove that beautifying and protecting your project go hand in hand.

The entire Jotun Facade line is engineered to resist harsh weather conditions, from wide temperature fluctuations and high humidity to rough sand abrasion, acidic rain and more. It is certified according to Qualicoat Class 1 and GSB Standard requirements, and has weathering performance in line with AAMA 2603.

Designed to last, these coatings come backed by the outstanding technical support Jotun is known for, as well as our 10-year Product Performance Guarantee* when used on aluminium following Jotun Powder Coatings guidelines.



THE LOOKS YOU'RE LOOKING FOR

Jotun Facade offers a wide range of colours, finishes and effects. Each Jotun Facade collection has been carefully designed to give you tailored benefits and greater freedom of design as you imagine your next project.









INCREASE YOUR LEED® POINTS

While representing a small fraction of your building's costs, the coatings you choose play a significant role in boosting rating points.

Jotun Facade is one of our Green Building Solutions* and has been independently tested for compliance with LEED® and BREEAM standards. Additionally, we have one of the most extensive lists in the coatings industry of product-specific, third-party-certified (Type III) EPDs, which are the most valuable for earning green building points.

Jotun Facade releases no harmful VOCs. It provides enhanced flow, reduced waste and improved mileage — all of which enable you to coat more and spend less.





SUPERIOR PERFORMANCE

DESCRIPTION	NORM	JOTUN FACADE
Impact resistance	EN ISO 6272/ ASTM D2794	Passes 23 inch-pounds or 2.5 Nm without film cracking.
Cupping test	EN ISO 1520	Passes 5 mm indentation without cracking.
Flexibility	EN ISO 1519	Passes 5 mm cylindrical mandrel bend test without cracking.
Acetic acid salt spray resistance	ISO 9227	Maximum 16 mm² infiltration over a scratch length of 10 cm after 1,000 hours.
Humidity resistance	EN ISO 6270-2	No infiltration exceeding 1 mm on both sides of the scratch after 1,000 hours.
Accelerated weathering	ISO 16474-3	Cycle: 4 hours at 50°C UV and 4 hours at 40°C condensation. No chalking, excellent gloss retention and colour stability after 300 hours testing.
Natural weathering test	ISO 2810 (South Florida, 27 °N)	No chalking, excellent gloss retention and colour stability after 12 months exposure (angle of 5° to South).
Flame spread index	ASTM E84	Class 1 or A
Smoke development index	ASTM E84	Class 1 or A


ALSO FROM JOTUN

JOTUN DURASOL

An ultra-premium coating with the highest possible weathering resistance.

JOTUN SUPER DURABLE

Strong weather protection with a wide range of aesthetic choices.



STAY IN TOUCH

At Jotun, we don't just sell a high-quality product; we back it up with the highest quality customer service. We are your partner in achieving your project's goals. With industry-leading technical support and a track record of global market experience, our aim is to not only meet, but exceed your needs.

Please contact your local Jotun representative to learn more about how our products can play an important role in your projects.

JOTUN.COM

